II. Specifications

Pickup Device	1/3" SONY Super HAD CCD
Video Format	NTSC or PAL
Scanning System	NTSC: 525 TV lines, 60 fields/sec PAL: 625 TV lines, 50 fields/sec.
Picture Elements	510 x 492 (NTSC) 500 x 580 (PAL)
Horizontal Resolution	380 TV lines
Sensitivity	0.3 Lux/F=1.2
S/N Ratio	Over 48dB (AGC off)
Electronic Shutter	1/50(1/60)~1/100,000
Gamma Correction	0.45
Video Output	BNC 1.0Vp-p,75 ohm
Sync. Mode	Internal Sync.
Lens Mount	M12 x P0.5
Power Source	12VDC
Power Consumption	3W max.
Dimensions	32mm x 32mm ; 1.28" x 1.28"
Weight	0.04kg; 0.09lbs
Operating Temperature	0°C~50°C; 32°F~122°F (20%~80% Humidity)
Certifications	FCC/CE



Your EverFocus product is designed and manufactured with high quality materials and components which can be recycled and reased. This symbol means that electrical and electronic equipment, at their end-of-life, should be disposed of separately from your household waste. Please, dispose of this equipment at your local community waste. Ihr EverFocus Produkt wurde entwickelt und hergestellt mit die qualitalit hochwer (gen Makerelt gen mit qualitalit hochwer (gen Makerelt und wieder verwendet werden konnen. Dieses Symbol bedutelt, dass nicht eine die dektronische Geräte mit für der Multungsdauer vom sollen. Jediterni entlängt werden sollen. Bette entsorgen Sie dieses Gerät bei Ihrer oftlichen kommunalen Steren der im Recytling selften.

MEB2G00100 VerA

EB200

INSTRUCTION MANUAL

1/3" CCD Camera Module

I. PIN Assignment

